

SW100SL ELECTRIC CUTTING UNIT




SW100SL. Professional cutting unit for Textile & Technical Textile applications.



ELECTRIC CUTTING UNIT

WHAT'S NEW:

New sharpening device system Easy fixing structure for O.E.M applications Low-friction Teflon® coated foot



Dimension layout







TECHNICAL DETAILS:

Blade diameter: 100 mm (4"), with hard

metal counterblade

Blade equipped: 10EHSS, 6-edges, HSS steel

Blade speed: 850 r.p.m.

Cutting ability: up to 35 mm (1.4") **Power:** single phase – 90 W Max. absorption: 2 A

Net weight: 2650 g (with power supply cord) Total weight (with packing box): 4750 g **Electric cable length:** 1.5 mt (with no plug) Minimum brightness for working

operations: LUX 200

Vibrations at start up: < 2.5 m/sec 2 **Temperature range:** $0 - 55 \, \text{C}$ **Umidity range:** 10 - 95% without

condensate

BLADE AVAILABLE:

10EHSS, 100 mm 6-edges, HSS steel | **10SEXTG**, 100 mm 4-edges, EXTRA steel | **10CSW**, 100 mm circular, HSS steel | 10EHSSTF, 100 mm 6-edges, HSS steel Teflon® coated | 10EMD, 100 mm 6-edges, Carbide (Widia®)



FOLLOW US:







RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 20161 Milan · Italy ph. +39 02 66 22 12 31 fax +39 02 66 22 12 93 info@rasor-cutters.com

www.rasor-cutters.com